



# UNLIMITED CREATION

## APPLICATION INSTRUCTIONS

# ReflexCut HT



ReflexCut HT is a very thin and stretchy high visibility reflective film. ReflexCut HT Silver 01, Neon Yellow 04 and ReflexCut HT FR 9 meet the EN ISO 20471 Class 2 standard. In addition, ReflexCut HT Neon Yellow 04 and FR 9 are flame retardant and meet as well the EN ISO 14116 and EN ISO 11612 standards.

Above all it is known for its excellent weeding properties.

### FEATURES:



Mirrored glass beads



150µ



Cotton, polyester, blended fabrics..  
Less suitable for nylon and other coated textiles.



60°C

### CUTTING CONDITIONS:



Blade 45 - 60°



low/medium



10 - 20 cm/s

### TRANSFER CONDITIONS:



150°C



15 s



medium/high



Cold peel

### ► PACKAGING



50 cm


25 m

50 cm


10 m

50 cm

5 m



1. Cut mirrored



2. Weed design



3. Transfer design



4. Remove liner, done !

Store in a cool and dry place; protect against the influence of light when stored. We recommend not to exceed a storage period of 12 months. The technical specifications rest on extensive tests and technical research. Due to the variety of possible influences during refinement, and use, the specifications should be viewed as reference values. We recommend a suitability test on the original material. A legally binding warranty of specific characteristics cannot be derived from our specifications.

SEF • 110 BD DENIS-PAPIN 53000 LAVAL – FRANCE  
TEL. +33 2. 43 53 36 48 FAX +33 2. 43 67 11 78  
www.seftextile.com E-mail: contact@sef-france.com  
SAS. CAPITAL € 945 000 RCS, LAVAL 304.802.291.00027







# UNLIMITED CREATION

## AVAILABLE COLORS


# ReflexCut HT



WHITE 2



GOLD 6




RED 3




BLUE 5



SILVER 1



BLACK 8



NEON YELLOW 4  
(flame retardant)



NEON PINK 7



FR 9 (flame retardant)

Store in a cool and dry place; protect against the influence of light when stored. We recommend not to exceed a storage period of 12 months. The technical specifications rest on extensive tests and technical research. Due to the variety of possible influences during refinement, and use, the specifications should be viewed as reference values. We recommend a suitability test on the original material. A legally binding warranty of specific characteristics cannot be derived from our specifications.

**S E F • 110 BD DENIS-PAPIN 53000 LAVAL – FRANCE**  
**TEL. +33 2. 43 53 36 48      FAX +33 2. 43 67 11 78**  
**www.seftextile.com E-mail: contact@sef-france.com**  
**SAS. CAPITAL € 945 000 RCS, LAVAL 304.802.291.00027**

